



SURVIVOR™ **BLAST HOSE**

Introducing the Survivor™ compound, now available for our family of blast hose. With twice the abrasion resistance*, Survivor™ compound outperforms typical blast hose! Survivor™ tube compound can be incorporated into just about any size or type of blast hose you are interested in extending the life of ... so request your quote today.

2X

THE LIFE OF STANDARD BLAST HOSES ON AVERAGE*

* Based on lab results from DIN test with non-rotating head versus abrasion-resistant SBR compounds. Service life may vary depending on application conditions.



WHAT DOES BLAST HOSE WITH 2X THE LIFE MEAN TO YOU?

- 1/2 the downtime due to changing hoses.
- Blast hose that can last through the big jobs.
- Whip hose that wears like standard blast hose.
- The right hose for the toughest applications.
- More production-time for automated machines with tough-to-change blast hoses.



HIGH-PRESSURE CAPACITY - 175 PSI MAXIMUM

BLAST HOSE COUPLINGS

NYLON - 125 PSI MAXIMUM



AVAILABLE SIZES	½	1	2	3	4	6
Standard 1¼ OR 50 mm Nozzle Holder	N/A	✓	✓	✓	N/A	N/A
Blast Hose Coupling	N/A	✓	✓	✓	N/A	N/A
Big-Gun / Full Port Blast Hose Coupling	N/A	N/A	N/A	N/A	N/A	N/A

ALUMINUM - 150 PSI MAXIMUM



AVAILABLE SIZES	½	1	2	3	4	6
Standard 1¼ OR 50 mm Nozzle Holder	✓	✓	✓	✓	✓	N/A
Blast Hose Coupling	✓	✓	✓	✓	✓	N/A
Big-Gun / Full Port Blast Hose Coupling	N/A	N/A	✓	✓	✓	✓

BRASS - 175 PSI MAXIMUM



AVAILABLE SIZES	½	1	2	3	4	6
Standard 1¼ OR 50 mm Nozzle Holder	✓	✓	✓	✓	✓	N/A
Blast Hose Coupling	✓	✓	✓	✓	✓	N/A
Big-Gun / Full Port Blast Hose Coupling	N/A	N/A	✓	✓	✓	✓

Coupling Size VERSUS Blast Hose Size		
Coupling/Nozzle Holder Size	Fits Black/Green Hose ID	Fits Tan Hose ID
05	1/2" (1 3/16 OD Only)	
1	3/4"	1"
2	1"	1 1/4"
3	1 1/4"	
4 / 4X	1 1/2"	
6X	2"	

Related Part	
	Part #: PB - 61173 Hose Cutters Ratcheting, 2 1/2" O.D. Max
	A MUST-HAVE tool for proper Coupling Assembly. Factory hose ends are not square - ALWAYS cut square before installing couplings or nozzle holders.